IN THE CLAIMS:

The text of all pending claims, (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with <u>underlining</u> and deleted text with <u>strikethrough</u>. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered).

Please AMEND claims 1, 12, 13, 16, and 24-26 and ADD new claim 30 in accordance with the following:

1. (CURRENTLY AMENDED) An input system, comprising:

an information generation part which generates generating input information based on a given input operation;

a transmission part which transmitstransmitting signals generated by having a plurality of different carrier frequencies modulated with the <u>same</u> input information; and

a reception part which receives receiving the transmitted signals and demodulates demodulating the signals into the <u>same</u> input information.

- 2. (ORIGINAL) The input system as claimed in claim 1, further comprising wave direction parts which are provided close to said transmission part so as to provide the signals transmitted from said transmission part with directivity.
- (ORIGINAL) The input system as claimed in claim 2, wherein said wave direction parts are antennas.
- 4. (ORIGINAL) The input system as claimed in claim 1, wherein said transmission part comprises a plurality of transmission circuits for transmitting the signals of the different carrier frequencies.
- 5. (ORIGINAL) The input system as claimed in claim 1, wherein said transmission part comprises:

an output part which successively outputs the different carrier frequencies; and a modulation part which has the different carrier frequencies modulated with the input information.

6. (ORIGINAL) The input system as claimed in claim 4, wherein each of the transmission circuit comprises:

an output part which outputs a corresponding one of the different carrier frequencies; and

a modulation part which has the corresponding one of the different carrier frequencies modulated with the input information.

- 7. (ORIGINAL) The input system as claimed in claim 1, wherein said reception part comprises a plurality of reception circuits for receiving the transmitted signals and demodulating the signals into the input information.
- 8. (ORIGINAL) The input system as claimed in claim 1, further comprising a pad member including conductive wire.
- 9. (ORIGINAL) The input system as claimed in claim 1, further comprising a conductive part,

wherein a user contacts said conductive part so that the signals transmitted from said transmission part are transmitted via said conductive part to the user.

10. (ORIGINAL) The input system as claimed in claim 1, further comprising:a conductive plate member; and

a conductive part, wherein said conductive part contacts said conductive plate member so that the signals transmitted from said transmission part are transmitted via said conductive part to said conductive plate member.


11. (ORIGINAL) The input system as claimed in claim 1, further comprising a plurality of wave direction parts for receiving the signals transmitted from said transmission part, said wave direction parts being provided on a side of said reception part.

12. (CURRENTLY AMENDED) An input system, comprising:

an information generation part which generatesgenerating input information based on a given input operation;

a transmission part which transmitstransmitting a signal signals generated by having a

3



a plurality of wave direction parts which are provided close to said transmission part so as to provide the signal-signals transmitted from said transmission part with directivity so that the same input information is transmitted alternately from the wave direction parts; and

a reception part which receives receiving the transmitted signal signals and demodulates demodulating the signal signals into the same input information.

(CURRENTLY AMENDED) The input system as claimed in claim 12, further 13. comprising:

a switching part which transmits transmitting the transmitted signal selectively to one of said wave direction parts based on a control signal supplied from said information generation part.

- (ORIGINAL) The input system as claimed in claim 12, wherein said transmission 14. part comprises a plurality of transmission circuits for transmitting the signal.
- (ORIGINAL) The input system as claimed in claim 12, wherein said wave 15. direction parts are antennas.
 - 16. (CURRENTLY AMENDED) An input device, comprising:

an information generation part which generatesgenerating input information based on a given input operation; and

a transmission part which transmitstransmitting signals generated by having a plurality of different carrier frequencies modulated with the same input information.

- 17. (ORIGINAL) The input device as claimed in claim 16, further comprising wave direction parts which are provided close to said transmission part so as to provide the signals transmitted from said transmission part with directivity.
- 18. (ORIGINAL) The input device as claimed in claim 17, wherein said wave direction parts are antennas.
- (ORIGINAL) The input device as claimed in claim 16, wherein said transmission 19. part comprises a plurality of transmission circuits for transmitting the signals of the different

carrier frequencies.

20. (ORIGINAL) The input device as claimed in claim 16, wherein said transmission part comprises:

an output part which successively outputs the different carrier frequencies; and a modulation part which has the different carrier frequencies modulated with the input information

21. (ORIGINAL) The input device as claimed in claim 19, wherein each of the transmission circuit comprises:

an output part which outputs a corresponding one of the different carrier frequencies; and

a modulation part which has the corresponding one of the different carrier frequencies modulated with the input information.

22. (ORIGINAL) The input device as claimed in claim 16, further comprising a conductive part provided on a surface of the input device,

wherein a user contacts said conductive part so that the signals transmitted from said transmission part are transmitted via said conductive part to the user.

23. (ORIGINAL) The input device as claimed in claim 16, further comprising a conductive part provided on

a bottom of the input device,

wherein said conductive part contacts a conductive plate member so that the signals transmitted from said transmission part are transmitted via said conductive part to the conductive plate member.

24. (CURRENTLY AMENDED) An input device, comprising:

an information generation part which generatesgenerating input information based on a given input operation;

a transmission part which transmitstransmitting a signal generated by having a plurality of different carrier frequencies frequency modulated with the same input information; and

a plurality of wave direction parts which are provided close to said transmission part so

as to provide the signal signals transmitted from said transmission part with directivity so that the same input information is transmitted alternately from the wave direction parts.

25. (CURRENTLY AMENDED) The input device as claimed in claim 24, further comprising:

a switching part which transmitstransmitting the transmitted signal selectively to one of said wave direction parts based on a control signal supplied from said information generation part.

- 26. (CURRENTLY AMENDED) The input device as claimed in claim 24, wherein said transmission part comprises a plurality of transmission circuits for transmitting the signal, the transmission circuits corresponding to the wave direction parts.
- 27. (ORIGINAL) The input device as claimed in claim 24, wherein said wave direction parts are antennas.
- 28. (PREVIOUSLY PRESENTED) The input system as claimed in claim 1, wherein said transmission part comprises a switching part that causes switching between the different carrier frequencies so that the different carrier frequencies are alternately modulated with the input information.
- 29. (PREVIOUSLY PRESENTED) The input system as claimed in claim 16, wherein said transmission part comprises a switching part that causes switching between the different carrier frequencies so that the different carrier frequencies are alternately modulated with the input information.
- 30. (NEW) An input device, comprising: an information generation part generating input information based on an input operation; and

a transmission part transmitting the same input information by a plurality of carrier frequencies.